

DUALIO CLOSED

Mozaïk / Serve-over counters


Serve-over




BEST ENERGY CLASS*




Product Categories



Cheese




Dairy products



Delicatessen



Meat



Pre-packed fish



Pre-packed fruit and vegetables



Chicken

Technical Features




High efficiency fans



LED lighting



Off-cycle defrost



Remote condensing unit



Ventilated

Follow us on: [f](#) [y](#) [in](#) [ig](#) by Epta

www.bonnetneve.com

DUALIO CLOSED

Mozaik / Serve-over counters

Serve-over

Product Range

DUALIO CLOSED (SLIDING & PUSH)											
Length-Lunghezza Longueur-Länge-Longitud mm		1250		1875		2500		3750		EOL 1650	EOL 1900
Width-Larghezza-Largeur-Breite-Ancho mm		E	M	E	M	E	M	E	M	E	M
LL-235		•	•	•	•	•	•	•	•	•	•
MAX LL-365		•	•	•	•	•	•	•	•	•	•
Display area Superficie di esposizione Warenpräsentationsfläche Surface d'exposition Superficie expositiva m2	STD LL235	1.87	2.17	2.82	3.26	3.74	4.33	5.61	6.50	1.57	1.79
	MAX LL365	1.93	2,23	2.91	3.38	3.86	4.45	5.80	6.68	1.70	1.89
Net storage capacity Capacità netta Nutzinhalt volume utile Capacidad neta dm3	STD LL235	288	350	434	528	575	700	863	1050	181	2.74
	MAX LL365	393	475	592	716	786	950	1178	1425	234	325
Loading area Superficie di appoggio Nutzfläche Surface de chargement Superficie de apoyo m2		2.06	2.36	3.09	3.54	4.12	4.72	6.18	7.08	1.6	2.06
End thickness Spessore spalla Stärke der Seitenwand Épaisseur de cheue joue Espesor lateral mm		50.00									


DUALIO CLOSED

Mozaik / Serve-over counters


Serve-over




Cross Sections




SILK C CLOSED - SLIDING




SILK C CLOSED MAX - SLIDING




SILK N CLOSED - SLIDING



SILK N CLOSED MAX - SLIDING



SILK N CLOSED EOL - SLIDING




Silk C Closed EOL - SLIDING


DUALIO CLOSED

Mozaik / Serve-over counters


Serve-over




SILK N CLOSED MAX EOL - SLIDING




SILC C CLOSED MAX EOL - SLIDING




SILK N CLOSED WITH BUMPER RAIL - SLIDING



SILK N CLOSED MAX EOL - PUSH



SILK N CLOSED - PUSH








SILK N CLOSED MAXI - PUSH

DUALIO CLOSED

Mozaik / Serve-over counters

Serve-over



DUALIO CLOSED

Mozaïk / Serve-over counters

Serve-over



*The information on the energy class (according to EU regulations 2019/2018 and EU 2019/2024) reported here refers to standard models and precise product configurations and set-ups. The site is based on the information available at the time of publication. As the energy class depends on the specific product configuration, despite the efforts made to ensure the greatest possible accuracy, the real data can differ significantly from the data declared here. For further information, we invite you to consult the European Product Database for Energy Labelling (EPREL) or to contact our Sales Office.