

SKYVIEW PLUS

Lenght-Lunghezza Longueur-Länge-Longitud mm		1250		1875		2500		3750		TG1510 Open		TG1510 Open		TG1370 Open or Closed		TG1810 Open or Closed		TG2000 Open or Closed		TG2310 Open		TG1510 Open		TG1330 Open		TG1810 Open		TG1960 Open		TG1960 Open		
		20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	
Altezza mm		20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	20	22	
SKYVIEW PLUS	Closed	C	•	•	•	•	•	•	•	•																						
		N	•	•	•	•	•	•	•	•					•	•			•	•												
		L	•	•	•	•	•	•	•	•									•	•												
	Open	C	•	•	•	•	•	•	•	•	•			•									•									
		N	•	•	•	•	•	•	•	•					•	•	•	•	•	•	•	•			•	•		•	•	•		
		L	•	•	•	•	•	•	•	•							•	•	•	•	•	•					•	•			•	•
Display area Superficie di esposizione Warenpräsentat- ionsfläche Surface d'exposition Superficie expositiva  m2	Closed	C	3.16	3.42	3.68	3.99	4.21	4.56	6.32	6.84	2.26		2.48																			
		N	3.33	3.59	3.88	4.19	4.44	4.79	6.67	7.19					3.38	3.63	2.84	3.17	4.49	4.82	3.67	4.10										
		L	3.42	3.68	3.99	4.35	4.56	4.91	6.84	7.34							2.92	3.25	4.91	5.29	3.77	4.21										
	Open	C	3.39	3.67	3.95	4.28	4.52	4.90	6.78	7.35	3.42											3.87										
		N	3.39	3.67	3.95	4.28	4.52	4.90	6.78	7.35							4.38								3.69	4.00	4.76		4.82	5.23		
		L	3.49	3.77	4.07	4.39	4.65	5.02	6.97	7.63																4.85	5.25			5.27	5.70	
Loading area Superficie di appoggio Nutzfläche Surface de chargement Superficie de apoyo  m2	Closed	C	1.35		1.6		1.85		2.75		1.21		1.21																			
		N	1.65		1.92		2.20		3.30						1.23	1.58	1.77	2.04														
		L	1.95		2.27		2.60		3.90							1.58	2.08	2.04														
	Open	C	1.35		1.6		1.85		2.75		1.21											1.21										
		N	1.65		1.92		2.20		3.30							1.58								1.23	1.58	1.77						
		L	1.95		2.27		2.60		3.90																1.58				2.08			
End thicktess Spessore spalla Stärke der Seitenwand Épaisseur de cheue joue Espesor lateral mm		30.00 (+ 35 Bumper Rail)																														