

SKYVIEW INTEGRAL PERFORM

Lenght -Lunghezza Longueur-Länge-Longitud mm		1250		1875		2500		3750		EOL 1960	
		AIR	WL	AIR	WL	AIR	WL	AIR	WL	AIR	WL
Altezza mm		2070		2070		2070		2070		2070	
SKYVIEW INTEGRAL PERFORM	Efficia	•				•		•			
	Modular	•	•	•		•	•	•	•	•	
	Volum	•				•		•			
Dispaly area Superficie di esposizione Warenpräsentationsfläche Surface d'exposition Superficie expositiva m2	Efficia	1.96				3.92		5.88			
	Modular	2.08	2.08	3.11		4.16	4.16	6.24	6.24	3.11	
	Volum	2.00				4.00		6.00			
Loading area Superficie di appoggio Nutzfläche Surface de chargement Superficie de apoyo m2	Efficia	1.08				2.17		3,24			
	Modular	2.52	2.52	1.94		5.05	5.05	7.56	7.56	1.94	
	Volum	1.46				2.92		4.38			
End thickness Spessore spalla Stärke der Seitenwand Épaisseur de che-que joue Espesor lateral mm	38.00 (+ 35 Bumper Rail) solid end 43.00 (+ 35 Bumper Rail) panoramic end										